



Livello

Professional Systems

Complete installation system for use with QA Luvanto flooring

- Fit it fast!**
 Livello can be laid over existing hard floor coverings, and with a strong adhesive already built-in fitting's really quick and easy - reducing installation time by up to 50%!
- Feels good to feet**
 Your feet are in for a treat - Livello's cushioning material makes your floor feel softer and warmer to walk on, and helps it absorb the impact if anything's dropped on it.
- Quiet please...**
 With brilliant sound reduction (23dB), Livello underlay deadens noise both in the room and underneath it, making a big difference to how your home feels.

Technical Data

Properties	Unit	Value	Test Method
Weight per square metre	kg/m ²	1.3	internal
Thickness	mm	3	internal
Density	kg/m ³	443	internal
Roll Size		1m x 15m (15m ²)	
Roll Weight	kg	20	
Thermal Resistance, R-Value	m ² k/W	0.035	BS4745:2005 (ISO 5085-1:1989)
	togs	0.0.6	
Impact Sound Reduction	dB	23	DIN ISO 140-8
Impact Sound Insulation Class	(IIC)	IIC55	ASTM/E4921 09

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.

QA Flooring Solutions Ltd

Block H, Pickerings Road,
 Widnes, Cheshire WA8 8XW
 Tel: 0151 495 3434
 Fax: 0151 420 9062
 Email: sales@qaflooringsolutions.com
 www.qaflooringsolutions.com

Simply Better

Heavy Traffic

Vinyl



Best for

Cushioning	Moisture Protection	Sound Reduction
Level Floors	Compression Recovery	Underfloor Heating
Hard Wearing	Heat Insulation	Commercial Use*

*Suitable for hotels and public buildings

Available in

Code	QAU-LVL-01
Size	1m x 10m (10m ²)
Thickness	3mm