

100%
recyclable PE
foam wood
underlay
offering
terrific value

Tooksiaal Data

■ Longer-lasting flooring

UniBase Bronze gives your floor covering the perfect level of support, to protect it from excess wear and even high impact damage – all of which helps your floor look good for longer!

Lightening the load

The ultra lightweight polyethylene foam material makes UniBase Bronze so easy to lift and manoeuvre...you won't believe just how much time and effort that can save you on every installation.

■ Faster fitting

There's no wasting time with UniBase Bronze - it's not only a lightweight to lift and move around, but really easy to cut and install so you can get on with the job.

lechnical Data			
Properties	Unit	Value	Method
Density	kg/m³	20 <u>+</u> 2.0	internal
Impact Sound Reduction	dB	≟ 19 (2mm)	BSEN ISO-140-8
Temperature Stability (unloaded)	°C	75	internal
Thermal Conductivity of PE Foam measured at 10°C	W/m k	0.045	DIN 4108
Thermal Resistance of PE Foam	$\mathrm{m}^2\mathrm{k/W}$	0.044 (2mm)	DIN 4108
		0.067 (3mm)	DIN 4108
Maximum Compression Load	kN/m²	≤ 2.0	DIN EN 1606
Resistance to Compression at 25% deformation	to/m²	<u>~</u> 2.0	DIN 53 577
Tensile Strength, lengthwise*	N/mm²	≥ 0.30	DIN 53 571
Tensile Strength, crosswise*	N/mm²	≥ 0.15	DIN 53 571
Elongation at break, lengthwise*	%	<u>~</u> 100	DIN 53 571

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.

<u>~</u> 80



Tel: 01484 411 885

Email: enquiries@flooringwarehousedirect.co.uk

www.flooringwarehousedirect.co.uk

Elongation at break, crosswise*

Simply Better

DIN 53 571

Light Traffic

Wood





Best for

Cushioning

Moisture Protection Sound Reduction

Level Floors

Compression Recovery Underfloor Heating

Hard Wearing Heat Insulation Commercial Use*

*Suitable for hotels and public buildings

Available in

Code	QAU-UBB-01
Size	1m x 10m (10m ²)
Thickness	2mm
Code	QAU-UBB-02
Size	1m x 15m (15m ²)
Thickness	2mm
Code	QAU-UBB-03
Size	1m x 15m (15m ²)
Thickness	3mm
Code	QAU-UBB-04
Size	1m x 25m (25m ²)
Thickness	2mm
Code	QAU-UBB-05
Size	1m x 120m (120m ²)
Thickness	2mm