



UniBase Gold

Underlay

Recyclable
PE foam
underlay
**with moisture
protection
and joint
sealing**

■ Lifelong supporter

The closed cell polyethylene foam fully supports your floor, helping to protect it and keeping it in good shape for a longer life.

■ Lightening the load

The lightweight material's not only a breeze to lift and move around, but also quick and easy to cut and install – saving time and effort during installation.

■ Protects against damp

Its metallised gold vapour barrier plus overlap and self adhesive strip means UniBase Gold protects your floor against moisture from the subfloor.

Technical Data

Properties	Unit	Value	Method
Density	kg/m ³	20 ± 2.0	internal
Impact Sound Reduction	dB	≥ 20	BSEN ISO-140-8
Temperature Stability (unloaded)	°C	75	internal
Thermal Conductivity of PE Foam measured at 10°C	W/m k	0.045	DIN 4108
Thermal Resistance of PE Foam	m ² k/W	0.067	DIN 4108
Maximum Compression Load	kN/m ²	≤ 2.0	DIN EN 1606
Resistance to Compression at 25% deformation	to/m ²	≥ 2.0	DIN 53 577
Tensile Strength, lengthwise*	N/mm ²	≥ 0.30	DIN 53 571
Tensile Strength, crosswise*	N/mm ²	≥ 0.15	DIN 53 571
Elongation at break, lengthwise*	%	≥ 100	DIN 53 571
Elongation at break, crosswise*	%	≥ 80	DIN 53 571

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.



Tel: 01484 411 885

Email: enquiries@flooringwarehousedirect.co.uk

www.flooringwarehousedirect.co.uk

Simply Better

Light
Traffic

Wood



Best for

Cushioning

Moisture
Protection

Sound
Reduction

Level
Floors

Compression
Recovery

Underfloor
Heating

Hard
Wearing

Heat
Insulation

Commercial
Use*

*Suitable for hotels and public buildings

Available in

Code QAU-UBG-01

Size 1m x 10m (10m²)

Thickness 3mm

Code QAU-UBG-02

Size 1m x 15m (15m²)

Thickness 3mm