



# WorkPro Slot

## Underlay

Closed cell  
polyolefin  
foam  
underlay  
designed for  
**maximum  
bonding**

### ■ Bond...max bond

The unique pre-cut perpendicular slots let you put beads of high strength elastic adhesive directly onto the subfloor, for the perfect bond with the floor covering.

### ■ Keep in shape

WorkPro Slot recovers quickly from compression – in other words, it always makes sure your floor's fully supported under even the heaviest load.

### ■ That warm feeling

By allowing a bond between the floor and subfloor, WorkPro Slot is ideal for laying over underfloor heating systems built into the subfloor.

### Technical Data

Properties	Unit	Value	Method
Impact Sound Reduction	dB	≈ 22	ISO 140-8
Thermal Resistance measured at 10°C	m <sup>2</sup> k/W	0.088	ISO 8301
Performance —	k Pa	3	EN 1606
Compressive Creep	kg/m <sup>3</sup>	300	EN 1363
The maximum load which can be applied to the underlay so that the loss in thickness remains below 10% after 10 years loading time.			
Joint Protection —	k Pa	28	ISO 844
Compressive Strength and measured at 0.5mm Deformation	kg/m <sup>3</sup>	2800	EN 13163

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.



Tel: 01484 411 885

Email: [enquiries@flooringwarehousedirect.co.uk](mailto:enquiries@flooringwarehousedirect.co.uk)

[www.flooringwarehousedirect.co.uk](http://www.flooringwarehousedirect.co.uk)

Heavy  
Traffic

Wood



### Best for

Cushioning

Moisture  
Protection

Sound  
Reduction

Level  
Floors

Compression  
Recovery

Underfloor  
Heating

Hard  
Wearing

Heat  
Insulation

Commercial  
Use\*

\*Suitable for hotels and public buildings

### Available in

**Code** QAU-WPS-01

**Size** 1m x 100m (100m<sup>2</sup>)

**Thickness** 3mm

**Code** QAU-WPS-02

**Size** 1m x 16.5m (16.5m<sup>2</sup>)

**Thickness** 3mm

**Simply Better**