

CRAFTSMAN

by **luvanto**

TECHNICAL DATA SHEET

Description & Classification	Test Method	Specification & Test Results			
Product Type	-	Craftsman Dryback LVT Plank	Craftsman Dryback LVT Herringbone	Craftsman SPC Plank	Craftsman SPC Herringbone
Dimensions	-	1227 x 187 mm	380 x 95 mm	1218 x 178 mm	625 x 125 mm
Thickness	-	2.0 mm	2.0 mm	5.0 mm (4.0 mm SPC + 1.0 mm IXPE)	5.5 mm (4.5 mm SPC + 1.0 mm IXPE)
Wear layer	-	0.3 mm	0.3 mm	0.3 mm	0.3 mm
System		Gluedown	Gluedown	l4F click	5Gi click
Packaging	-	20 pcs/pack 70 packs/plt	60 pcs/pack 144 packs/plt	10 pcs/pack 40 packs/plt	20 pcs/pack 72 packs/plt
Weight	-	17.32 kg/pack	8.16 kg/pack	18.63 kg/pack	14.89 kg/pack
Warranty - Residential / light commercial	-	20 / 10 years	20 / 10 years	20 / 10 years	20 / 10 years
Level of use - Heavy domestic	EN ISO 10874	Class 23	Class 23	Class 23	Class 23
Level of use - Moderate commercial	EN ISO 10874	Class 31	Class 31	Class 31	Class 31
Formaldehyde emission	EN 717-1	E1	E1	E1	E1
Reaction to fire	EN 13501-1	Bfl-s1	Bfl-s1	Bfl-s1	Bfl-s1
Slip resistance	EN 13893	R9	R9	R9	R9
Pendulum test for slip resistance	BS7976-2:2002	Wet 52 Dry 68	Wet 52 Dry 68	Wet 52 Dry 68	Wet 52 Dry 68
Resistance to staining	EN 438-2:2016	Class 5 Not affected	Class 5 Not affected	Class 5 Not affected	Class 5 Not affected
Light stability	ISO 105-B02	≥Grade 6	≥Grade 6	≥Grade 6	≥Grade 6
Antistatic resistance	EN 1815	-	-	< 2kV	< 2kV
Castor chair	EN ISO 4918	Pass	Pass	Pass	Pass
Effect of furniture leg	EN ISO 16581	-	-	No visible damage	No visible damage
Residual indentation	ISO 24343-1	≤0.1 mm	≤0.1 mm	≤0.3 mm	≤0.3 mm
Dimension stability and curling after exposure to heat	ISO 23999	≤0.15%	≤0.15%	Dimension stability ≤0.15% Curling ≤1 mm	Dimension stability ≤0.15% Curling ≤1 mm
Wear resistance	ISO 24338	-	-	≥2000 cycles	≥2000 cycles
Impact resistance	EN 13329	-	-	≥800 mm	≥800 mm
Micro-scratch resistance	EN 16094	-	-	MSR-A1	MSR-A1
Thermal resistance	EN 12667	0.039 (m²K)/W	0.039 (m²K)/W	0.045 (m²K)/W	0.055 (m²K)/W
VOC Emission	ISO 16000	A+	A+	A+	A+
CE		Certified	Certified	Certified	Certified
UKCA		Certified	Certified	Certified	Certified
Floorscore		Certified	Certified	Certified	Certified
Indoor Air Comfort Gold		Certified	Certified	Certified	Certified
Utilization		Recyclable	Recyclable	Recyclable	Recyclable

