

A close-up photograph showing a hand placing a long, rectangular wood-look laminate plank onto a floor. The floor is covered with a grid of adhesive, visible as a series of concentric circles and lines. The plank has a natural wood grain pattern. The background shows more of the same flooring material already installed.

**luvanto**  
FLOORING FOR LIFE

**Universal Adhesive &  
High Temperature Adhesive**

# **Strength & Performance For Peace Of Mind**

Luvanto Universal & High Temperature Adhesives are designed and approved for the rapid and reliable installation of dryback Luvanto LVT flooring and acoustic underlays; more fitter friendly with higher initial grab, faster drying and high strength when fully set. Pull-off tests have shown that the smoothing compound will fail before the adhesive.

Luvanto Universal & High Temperature Adhesives are low-emission, solvent-free and odourless; and are suitable for underfloor heating, areas of high footfall and castor wheel traffic.

## **Luvanto Universal Adhesive**

Luvanto Universal Adhesive is a fully hybrid adhesive which is suitable for high temperature areas, when it is applied wet set, including underfloor heating systems and areas of direct sunlight. It can also be used for pressure sensitive applications. It can be used to bond acoustic underlays to the subfloor. One product for all applications.

### **Key Benefits:**

- Powerful initial grab – commended by fitters who have worked with it
- Long working time
- High strength when fully set
- Suitable for areas of high footfall and castor wheel traffic
- Will not lose bonding strength at high temperature – up to a structural surface temperature of 50°C (subject to the limitations of the substrate and floorcovering)
- EC1+ rated on its VOC emissions (safest rating in the world).

## **Luvanto High Temperature Adhesive**

Luvanto High Temperature Adhesive is a high-performance wet set adhesive designed for high temperature applications, including underfloor heating systems and areas of direct sunlight.

### **Key Benefits:**

- Strong initial grab
- Very long working time
- High strength when fully set with high tolerance to moisture
- Suitable for areas of high footfall and castor wheel traffic
- Non flammable
- EC1+ rated on its VOC emissions (safest rating in the world).

Luvanto Universal and High Temperature Adhesives are approved for use with Luvanto LVT flooring and are covered by the Luvanto Warranty.

Shelf life is 12 months.



### Luvanto Universal Adhesive

| Product Code | Tub Size | Coverage per Tub      | Pallet Quantity | RRP Inc VAT |
|--------------|----------|-----------------------|-----------------|-------------|
| QAA-ADH-U1   | 5kg      | 18-22m <sup>2</sup> * | 72              | £79.99      |
| QAA-ADH-U2   | 10kg     | 36-44m <sup>2</sup> * | 44              | £129.99     |

### Luvanto High Temperature Adhesive

| Product Code | Tub Size | Coverage per Tub      | Pallet Quantity | RRP Inc VAT |
|--------------|----------|-----------------------|-----------------|-------------|
| QAA-ADH-H1   | 6kg      | 22-26m <sup>2</sup> * | 72              | £79.99      |
| QAA-ADH-H2   | 12kg     | 44-53m <sup>2</sup> * | 44              | £129.99     |

\* Based on using an A2 Notch Trowel, subject to the substrate condition and the backing and type of the flooring being installed.

For more information, trade pricing or to place an order call us on 0151 427 6000 or email [sales@luvanto.com](mailto:sales@luvanto.com)

[www.luvanto.com](http://www.luvanto.com)



**Luvanto – QA Flooring Solutions Ltd**  
Unit 2 Hurricane Drive, Liverpool, L24 8RL.  
0151 427 6000   sales@luvanto.com

**[www.luvanto.com](http://www.luvanto.com)**